



LUXOMAT[®]net RM-DALISYS-1C-REG

Description	Colour	Part number	EAN number
RM-DALISYS-1C-REG	white	92849	4007529928491



:-|

Accessory	Colour	Part number	EAN number
PS-DALISYS-USB-REG	white	92843	4007529928439

■ TECHNICAL DATA

Settings	DIP-switch, HEX-switch, B.E.G. BLE App, B.E.G. PC-Tools, B.E.G. DALI Router
Voltage:	10 - 22 V DC via DALI Bus
Power supply:	7 mA
Degree / class of protection:	IP20 / Class II / CE
Dimensions:	1 TE / 63 x 18 x 85mm
Ambient temperature:	-25 °C to +50 °C
Housing:	Polycarbonate, UV-resistant
	Relay
Switching power:	3000 W, $\cos \varphi = 1$ / 1500 VA, $\cos \varphi = 0,5$; μ -contact
Dali:	DALI
Time settings:	1 min - 150 min, just in Cut-off- and HVAC-mode
Switch-on delay:	1 to 150 min. (only in HVAC mode)

PRODUCT INFORMATION

- DINrail DALI relay module with 1 switching channel
- High-output and potential-free contact for loads with high inrush current
- Seamless integration in B.E.G. LUXOMAT[®]net DALI SYSTEM
- Integrated application controller with different operating modes
- Operating modes: Standard, Cut-off, HVAC, Impulse, Alarm
- DIP- and HEX-switch for quick commissioning with basic functionality
- Full range of functions can only be activated with other products of the product group B.E.G. LUXOMAT[®]net DALI SYSTEM.



LUXOMAT®net

RM-DALISYS-1C-REG

DIMENSIONS DRAWING

