

KATLA BL



Aluminium

Aluminium carrier for good thermal management

Variable

PRACHT-CLIP-SYSTEM for variable mounting

IK08

Co-extruded polycarbonate housing

Quick connection

Due to clippable end caps and PRACHT SLIDER

Sealed

Extremely short silicone seals

Incl. Wiring

Factory-made 3x1.5mm² through-wiring

MULTITALENT

PRICE/PERFORMANCE SLIM
SOLID PROFILE LIGHT
EASY INSTALLATION HOMOGENEOUS LIGHT
1:1 REPLACEMENT ENEC

HOUSING Co-extruded polycarbonate, impact resistant, IK08.

SEALS Extremely short, age-resistant silicone seals.

ELECTRICAL COMPONENTS High power LED, LED converter.

THROUGH-WIRING Including 3x1.5mm² wiring ex works.

ASSEMBLY Variable mounting distances with PRACHT-CLIP-SYSTEM. Suitable for ceiling and rail mounting.

FIELDS OF APPLICATION Parking garages, basements, workshops, 1:1 fluorescent light-exchange.

Individual luminaire, color temperature 4000 K, Ra>80, IP65

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x23W	120° wide	2800lm	5231004	1240mm	1.1kg
1x45W	120° wide	5400lm	5231014	1240mm	1.1kg
1x34W	120° wide	3800lm	5231005	1540mm	1.2kg
1x54W	120° wide	6500lm	5231015	1540mm	1.2kg

3
YEAR WARRANTY

50.000 h
OPERATIONAL LIFETIME

ENERGY EFFICIENCY CLASS
A++

IP65

INCL. DV (DALI/DMT)

D

-20°C ... +35°C