

PRACHT®

# TUBIS BL

PRACHT®



Incl. DV

Factory-made 3x1.5 mm<sup>2</sup> through-wiring

NOBLE

Stainless steel clamps

Aluminium

Aluminium carrier for optimal thermal management

Resistant

High-quality PMMA-blend round tube (IK06, Ø70 mm)

Breathing

No condensation thanks to climate membrane

Fast

Solid PBT end caps, extremely fast connection

**HOUSING** PMMA-Blend round tube.

**END CAPS** Solid PBT end caps.

**SEALS** Extremely short, age-resistant silicone seals.

**ELECTRICAL COMPONENTS** High power LED, LED converter.

**ASSEMBLY** Variable mounting distances by PRACHT-CLAMP-SYSTEM. Suitable for ceilings, wall, pendant and rail mounting.

**FIELDS OF APPLICATION** Washing plants, wet rooms, workshops, acid and alkaline cleaning plants and oily environments, 1:1 fluorescent light-exchange.

**Individual luminaire, color temperature 4000 K, Ra>80, diameter 70mm**

Power	Light distribution	Luminous flux	P/N	Length	Weight
1x24 W	135° wide	2800 lm	5240004	1310 mm	1.8 kg
1x45 W	135° wide	5400 lm	5240014	1310 mm	1.8 kg
1x32 W	135° wide	3800 lm	5240005	1610 mm	2.2 kg
1x54 W	135° wide	6500 lm	5240015	1610 mm	2.2 kg

# WATER SPORTSMAN

**TIGHT ACID-ALKALI-RESISTANT  
TUBULAR LUMINAIRE  
STURDY FAST ASSEMBLY ENEC  
FOR UNPROTECTED OUTDOOR AREAS**

**MODERN DESIGN**

**3**  
YEAR WARRANTY



**50.000 h**  
OPERATIONAL LIFETIME



**A++**

**IP67  
IP69K**



**INCL. DV  
(GALSHPP)**



**-20°C ... +40°C**

**Protection class I according to EN 60598**  
**Protection type IP67/IP69K**  
 AC/DC 220-240 V 50/60 Hz \*registered

PRACHT.COM

+49 64 66 / 91 40 -0