


Product information

LT-Kabel-I-8-OM4-Cca

R844135
2000 m



This cable can be used for LAN and WAN backbones, telecom access lines, fiber to business and fiber to the building drop connections as well as fiber to the home drop and access connections. With its LSZH sheathing this cable is ideal for mixed indoor and outdoor installations. It is equally suited for installation in ducts and trays. The cable is well suited for installation in tubes.

- Sheath: 1.0mm LSZH UV resistant
- Colour: Green

030.1402.1 / similar product

Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	ISO 11801:2011 EN 50173-1 IEC 60794-2-20 IEC 60332-1-2 IEC 60754-1 IEC 60754-2 IEC 61034-2 CPR fire class: EN50575
Cable type	loose tube
Jacket material	LSZH
Fire rating	Cca
Cable protection	Waterblocked E-Glass fiber elements
Cable overall diameter	6.0
Cable design	U-DQ(ZN)BH
Fiber type	multimode (MM)
Fiber class	OM4
Number of fibers	8
Conductor type	loose tube, gel-filled
Fiber diameter	G50 / 125 µm

Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	2000 m
Color	green