

PRACHT®
PRO LINE

SOFT SHELL



THE MUCH-LOVED

A BERRY WITH CORE COMPETENCIES

From a botanical point of view, it is indeed a berry, and the pit at its core makes it strong.

Shell and core are not edible, but between those two parts is where the treasure of an avocado can be found. The fruit pulp, enclosed by shell and pit.

The fruit pulp glows in a green to golden yellow color and, when sprinkled with lemon or lime juice, it retains this color despite the usual open-air oxidation process - even when the fruit is already cut open.

AVOCADO.

AN INTERNATIONAL FRUIT.

VERSATILE IN ITS CHARACTERISTICS.

WHAT MAKES THE AVOCADO SUCH A POPULAR FRUIT?

►The Avocado is a source of healthy fats that play a role in our cardiovascular health. Not every healthy oil is heat-stable. Avocado oil is! With a low content of carbohydrates, the fruit pulp of the avocado provides many vitamins and nutrients. They are beneficial against inflammatory changes.


The Avocado is particularly suitable as a spread and for dipping.

►Avocados look pleasing to the eye and their properties put others in the best light: users speak of times where they experienced skin improvements when applying avocado cream or oil.

The Avocado is well-suited for external use.

IT HAS A VARIETY OF GREAT FEATURES.

AVOCADO




PRACHT®

PRO LINE

... EXCEPTIONAL TALENTS.

MADE IN GERMANY
UNCOMPROMISING SERVICE
EXCHANGEABLE COMPONENTS HIGHEST QUALITY
INDIVIDUALLY CUSTOMIZABLE
VERY HIGH DURABILITY




INEXPENSIVE
HIGH DURABILITY
ON-HAND
CERTIFIED
HIGH QUALITY

BASIC LINE

... REAL STARTERS.

PRACHT®



PRACHT®

APOLLO

N LED | LED INDUSTRY | XT

HOUSING slim, fully sealed luminaire housing made of glass fibre reinforced polyester, white, substantially acid and alkali resistant.

LAMP HOLDER END PIECES single piece push-fit lamp holders made of PBT, shatter proof, with clips made of stainless steel.

LAMP COVER with parabolic mirror reflector, swivelling, made of PRACHTOPAL (impact resistant) or clear PMMA (deep 30°).

SEALS short, ageing resistant silicone seals.

ELECTRICAL COMPONENTS high performance LEDs, built-in converter.

THROUGH-WIRING 7x2.5 mm² max. available.

INSTALLATION variable mounting points due to PRACHT-CLIP-SYSTEM made of stainless steel. Suitable for ceiling, pendant and horizontal wall mounting. Optionally available as a recessed version.

FIELDS OF APPLICATION industrial halls, logistic centres, cold storage facilities, workshops, maintenance and production halls.

PRACHT®

DURABLE **PRALUX** INSTANT HIGH LUMINOUS FLUX
EFFICIENT EASY MAINTENANCE
ENERGY-SAVING **POWER**
SWIVELLING INDUSTRIAL COMPONENTS



FLAGSHIP

EMBODIMENT

| Model | Description |
|---------------------|--|
| APOLLO N LED | Swivelling linear luminaire with thermic decoupled components. Higly resistant and effective - therefore very versatile. |
| APOLLO LED INDUSTRY | The industry market has even higher expectations. Thanks to its industry components the luminaire can be used where other lights go out. |
| APOLLO XT | We made our best luminaire even better. Now available with extensions. Spectral lighting, sensors as well as full connectivity. |



APOLLO N LED
single lamp




APOLLO N LED
twin lamp



APOLLO N LED
easy mounting



Protection class I or II in accordance with VDE 0711/EN 60598
Ingress protection IP65
Dust-tight, water jet proof, 220-240V 50/60 Hz
(depending on model)



5
YEAR
WARANTY

UP TO
100.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS
A++

P
PRALUX
MIRROR TECHNOLOGY

FROM -45°C TO +40°C
DEPENDING ON MODEL

PRACHT.COM

+49 64 66 / 91 40 - 0

PRACHT®

ARKTIS | KENIA

ARKTIS LED | KENIA LED

HOUSING Slim, fully sealed luminaire housing made of glass fibre reinforced polyester, white, substantially acid and alkali resistant.

LAMP HOLDER END PIECES Single piece push-fit lamp holders made of PBT.

SOCKET Two-slot plug-in socket with silver plated contacts.

LAMP COVER With parabolic mirror reflector, swivelling, made of PRACHTOPAL (impact resistant).

SEALS Short, ageing resistant silicone seals.

ELECTRICAL COMPONENTS High performance LED with industrial grade driver.

THROUGH-WIRING 7x2.5 mm² max. available.

INSTALLATION Variable mounting points due to PPRACHT-CLIP-SYSTEM made of stainless steel. Suitable for ceiling, pendant and horizontal wall mounting.


FIELDS OF APPLICATION Cold and deep-freeze storage facilities, industrial halls, logistic centres.



FRONTIERSMAN

EMBODIMENT

| Model | Description |
|------------|--|
| ARKTIS LED | Linear luminaire with thermic uncoupled, particularly cold insensitive components. The perfect linear illumination with swivelling reflectors for cold surroundings. |
| KENIA LED | High temperatures and high humidity - the right luminaire for that purpose. The luminaire has IP65 and special components for such areas of expectation. |



ARKTIS LED




KENIA LED
twin lamp



KENIA LED
single lamp



Protection class I or II in accordance with VDE 0711/EN 60598
Ingress protection IP65
Dust-tight, water jet proof, 220-240V 50/60 Hz
(depending on model)



5
YEAR
WARRANTY

AT+65°C
50.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS
A++

FROM -45°C TO +40°C
DEPENDENT ON MODEL

P
PRALUX
MIRROR TECHNOLOGY

LED

PRACHT.COM

+49 64 66 / 91 40-0

PRACHT®

LUNA N LED | N LED WET

HOUSING polyester, grey, glass fibre reinforced.

LAMP COVER LOPRA® for glare-free and homogeneous light distribution.

SEALS ageing resistant silicone foam.

ELECTRICAL COMPONENTS high performance LEDs, LED converter.

THROUGH-WIRING 5x2.5 mm² max. available, knock outs for cable entry on the ceiling side plus one on either end.

INSTALLATION variable mounting points through PRACHT CLIP SYSTEM made of stainless steel, suitable for ceiling, pendant and trunking rail mounting.

FIELDS OF APPLICATION parking garages, cellar rooms, workshops, cold environments, unprotected outdoor areas

PRACHT®

UNPROTECTED OUTDOOR AREAS
DURABLE INSTANT HIGH LUMINOUS FLUX
EFFICIENT HIGH PROTECTION CLASS
SILICONE FOAM SEAL ENERGY-SAVING
WET



EMBODIMENT

| Model | Description |
|----------------|--|
| LUNA N LED | Long established in the market. The classic among the diffuser luminaires - for good reasons: High quality, silicone foam sealing, versatile applications and adaption. Speaks for itself. |
| LUNA N LED WET | The classic with LOPRA casing for anti-glare and homogeneous illumination. Due to the usage of the climate membrane it is suitable for unprotected outdoor areas. |



LUNA N LED
WET



LUNA N LED



LUNA N LED



Protection Class I in accordance with EN 60598
Ingress protection IP66

Dust-tight, water jet proof, 220-240V/50/60 Hz
(depending on model)



5

YEAR
WARRANTY
DEPENDENT ON MODEL



50.000 h
LIFETIME
DEPENDENT ON MODEL



A++



FROM -20°C TO +35°C
DEPENDENT ON MODEL

IP66



SILICONE
FOAM SEAL



UNPROTECTED
OUTDOOR AREA
(OPTIONAL)

PRACHT.COM

+49 64 66 / 91 40-0

PRACHT®

TARA

TRUNKING Corrosion-resistant aluminum, 60 mm x 45 mm (w/h).

LAMP COVER With Parabolic mirror reflector, pivotable, made of PRACHTOPAL® (impact resistant) or PMMA clear.

HOLDER END PIECES One-piece pressure cover, holder end pieces made of PBT, shatter proof, with clips made of stainless steel.

SEALS Short, ageing resistant silicone seals.

THROUGH-WIRING Ex works 7x2,5 mm² preassembled.

ASSEMBLY Quick assembly due to modular prefabrication from 1670mm up to 4995mm pieces.

FIELDS OF APPLICATION Industrial halls, logistic centres, high-bay warehouses, cold storage facilities, food industry.

PRACHT®

EASY CONNECT LIGHT STRIP FLEXIBLE IP65 LOW-MAINTENANCE PRALUX MODULAR UP TO +45°C



INDUSTRY LINESMAN

EMBODIMENT

| Model | Description |
|-------|---|
| TARA | The first real continuous-row industry luminaire with IP65 and swivelling reflectors. Extremely tough due to a aluminium mounting rail and the long established swivelling Parabol-mirror-reflectors. |



TARA
luminaire insert twin lamp



TARA
single lamp



TARA
twin lamp

5
YEAR
WARRANTY

AT+65°C
50.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS
A++



PRALUX
MIRROR TECHNOLOGY

FROM
UP TO
-20 °C
+45 °C

IP65

PRACHT.COM

+49 64 66 / 91 40 - 0



PRACHT®

TUBIS

LED INDUSTRY | N LED
N LED FARMER | XT

HOUSING Tubular housing, fully sealed, made of PO (PRACHTOPAL®), PMMA (impact-resistant), PC (polycarbonate, shockproof), Silicateglass, substantially acid and alkali resistant, dia. 90 mm.

SEALS Short, ageing resistant silicone seals.

ELECTRICAL COMPONENTS High performance LEDs, built-in converter.

THROUGH-WIRING 5x2.5 mm² max. available, depending on model.

INSTALLATION Variable mounting points due to PRACHT stainless steel clamps. Suitable for ceiling, pendant, horizontal and vertical wall mounting.

FIELDS OF APPLICATION Unprotected outdoor areas, industrial and washing bays, high humidity areas.



EMBODIMENT

| Model | Description |
|--------------------|---|
| TUBIS N LED | Versatile applicable tubular luminaire. Audited in IP66/68/X9K. Unhesitant application in wet areas thanks to short sealing surfaces made of high quality, ageing resistant silicone. |
| TUBIS N LED FARMER | Fully glued tubular housing for unhesitant application in cattle breeding. Withought through wiring. DIM-DALI possible. |
| TUBIS LED INDUSTRY | Particularly resistant industry components, good thermic management and available in different designs. The best solution for the highest expectations. |
| TUBIS XT | Extremely dense for very wet areas. Now available with extensions. Spectra lighting, sensors as well as full connectivity. |



Protection Class I
Ingress protection IP68/IPX9K
Dusttight, water pressure tight, 230V/50 Hz *application pending
(depending on model)



PRACHT®

ENERGY-SAVING
WATER PRESSURE TIGHT
IP66/IP68/IPX9K
UNPROTECTED OUTDOOR AREAS
CATTLE BREEDING DUST-TIGHT
FOOD LIVESTOCK FARMING
INDUSTRY

WATER LOVER



P0-Tubular housing
TUBIS N LED und INDUSTRY



PC-/SG-Tubular housing
TUBIS LED INDUSTRY



P0-Tubular housing
TUBIS N LED FARMER

5

YEAR
WARRANTY



100.000 h
LIFETIME



A++



LIVESTOCK FARMING
OPTIONAL



FROM -30°C UP TO +50°C
DEPENDING ON MODEL



UNPROTECTED
OUTDOOR AREA
DEPENDING ON MODEL

IP66
IP68
IPX9K

PRACHT.COM

+49 64 66 / 91 40 - 0

PRACHT®

TINOS N LED

HOUSING round tubular housing, closed from all sides made of PRACHTOPAL® (PMMA, impact resistant). Highly acid and alkali resistant, ø60mm.

SEALS short, ageing resistant seals made from silicone.

ELECTRICAL COMPONENT high power-LEDs, converter.

WIRING max. 5x1,5mm² is possible.

ASSEMBLY variable mounting distances due to PRACHT stainless steel clamps.

INSTALLATION suitable for ceilings, suspended, horizontal and vertical wall mounting.

FIELDS OF APPLICATION unprotected outdoor areas, industrial and washing facilities, areas with high humidity.



SCUBA INSTRUCTOR

EMBODIMENT

| Model | Description |
|-------------|---|
| TINOS N LED | Slim, efficient tubular luminaire with short sealing system made of ageing resistant silicone. Certified with IP68 and 69K up to 2m depth. In special versions with stainless steel caps, suitable especially for architecture. |



TINOS N LED




TINOS N LED



TINOS N LED



Protection class I
Ingress protection IP68/IPX9K
dust proof, water pressure tight, 220-240 V 0/50/60 Hz



5

JAHRE
GARANTIE



AT+65°C
100.000 h
LIFETIME



A++



FROM -30°C UP TO +50°C
DEPENDENT ON MODEL

IP68
IP69K

PRACHT.COM

+49 64 66 / 91 40-0

PRACHT®

KATLA

INDUSTRY | NAWAROH | XT

HOUSING Translucent, impact resistant opalized housing made of one piece.

SEALS Frontal age-resistant short silicone seals.

ELECTRICAL COMPONENTS High performance LED, built-in converter, easy exchange.

THROUGH-WIRING Standard built-in through wiring 3x1.5 mm².

INSTALLATION Variable mounting due to PRACHT-Clip-System. Easy access power supply spaces (with plug-in).

FIELDS OF APPLICATION Parking decks, logistic centres, basements, factories.

PRACHT®

HIGH INGRESS PROTECTION **CEILING BRIGHTENING**
SUSTAINABLE EASY EXCHANGE OF COMPONENTS
1:1 EXCHANGE **QUICK INSTALLATION**



FRONT RUNNER

EMBODIMENT

| Model | Description |
|----------------|---|
| KATLA | Brilliantly simple solution due to slim IP66 protected luminaire housing with extremely comfortable cable connection area. Particularly suitable for the illumination of dark ceilings. |
| KATLA INDUSTRY | The industry market has even higher expectations. Thanks to industry components that's no problem. |
| KATLA NAWAROH | Out of love for the environment - the material Durabio, developed by PRACHT, makes it even more resistant. Largely acid and alkali resistant, UV-resistant and IP66. Up to 60% of the material are made of renewable raw materials. (NAWAROH®). |
| KATLA XT | The luminaire industry doesn't remain at a standstill - neither do we. Now available with extensions. Spectral lighting, sensors as well as full connection. |



KATLA



KATLA



Grid connection




Protection class I in accordance with EN 60598

Ingress protection IP66

Dustproof, water jet proof

220-240V 50/60 Hz



5
YEAR
WARRANTY

AT+65°C
50.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS
A++

FROM -20°C UP TO +40°C
DEPENDENT ON MODEL

IP66

UNPROTECTED
OUTDOOR AREA
DEPENDENT ON MODEL

PRACHT.COM

+49 64 66 / 91 40 - 0

PRACHT®

QUADRONIUS

INDUSTRY | HT

HOUSING Die cast aluminium, white coating

LAMP COVER Safety glass (ESG), polycarbonate (PC, shatter proof), LOPRA® or PC Opal.

SEALS Short, ageing-resistant silicone seals.

ELECTRICAL COMPONENTS High performance LED converter.

INSTALLATION Pendant mounting, direct ceiling or wall mounting with optional wall/ceiling mounting bracket.

OPTIONS Other housing color, four-lamp version, emergency light function, daylight and motion control sensor.

FIELDS OF APPLICATION Logistic centres, industrial halls, cold storage facilities (-40°C), high-rack warehouses. Optional: Unprotected outdoor areas, sports arenas, high temperature, livestock farming, swimming pools.



QUADRONIUS INDUSTRY/HT
single lamp



QUADRONIUS INDUSTRY/HT
twin lamp

EMBODIMENT

| Model | Description |
|---------------------|---|
| QUADRONIUS | Our high bay spotlight symbolizes performance strength, efficiency and high adaptability. Not only is he applicable in the nearly typical application areas, like high bay storages, industrial halls and production halls, but also in limited areas of animal keeping as well as the food industry. |
| QUADRONIUS INDUSTRY | The industry market has even higher expectations. Thanks to industry components that's no problem. |
| QUADRONIUS HT | Particularly suitable for the extremely hot surroundings. Thanks to the optimized structure this high bay spotlight withstands temperatures up to 75°C. |

MUSCLEMAN



QUADRONIUS
single lamp on/off



QUADRONIUS
twin lamp on/off



QUADRONIUS WET
single lamp

5
YEAR
WARRANTY


100.000 h
LIFETIME

ENERGY
EFFICIENCY
CLASS
A++

-40 °C ... +75 °C
(DEPENDING ON MODEL)


IP65

UNPROTECTED OUTDOOR
AREAS (OPTIONAL)



Protection Class I in
accordance with VDE
0711/EN 60598, Ingress
protection IP65

Dustproof, water jet proof, 220-240V, 50/60Hz, *up to +60°C
(depending on model)



PRACHT.COM

+49 64 66 / 91 40 - 0

LUNA BL



ALLROUNDER

EXTREMELY FAST ASSEMBLY
DIFFUSER LUMINAIRE
HIGH QUALITY
PRICE / PERFORMANCE DUST-TIGHT
1:1 REPLACEMENT HOMOGENEOUS LIGHT

KATLA BL



MULTI-TALENT

SOLID SLIM
PRICE / PERFORMANCE
PROFILE LUMINAIRE
EASY INSTALLATION HOMOGENEOUS LIGHT
1:1 REPLACEMENT



EFFICIENT LOW MAINTENANCE
JET-PROOF
DUST-TIGHT **DURABLE** PRICE / PERFORMANCE
DIM-DALI UP TO 134 LM/W

COMO



HQL KILLER

BASIC LINE: THE HARD CORE

INTRODUCING OUR HARD CORE
PRODUCTS – PRACHT'S BASIC LINE:
EXCELLENT PRICE-PERFORMANCE
RATIO, QUICK AVAILABILITY - TOGETHER
WITH OUR RENOWNED PRACHT QUALITY
AND IN A HIGH PROTECTION CLASS.

THE STRONG SUPPORTERS BEHIND OUR PRO LINE.

3

YEAR
WARRANTY



50.000 h
OPERATIONAL LIFETIME



A++

TUBIS BL




WATERPROOF

TIGHT ACID-ALKALI-RESISTANT
TUBULAR LUMINAIRE
STURDY FAST ASSEMBLY
FOR UNPROTECTED OUTDOOR AREAS
MODERN DESIGN

PRACHT[®]
CITY LINE

THINK ABOUT
TOMORROW TODAY.



FOR MORE INFORMATION: [PRACHT.COM](http://pracht.com)

**„THERE WILL NEVER BE ANY COMPROMISE
IN THE QUALITY OF MY PRACT LUMINAIRES.“**

Alfred Pracht, Founder, 1963