



AGAT SLIM LED

Recessed luminaires



Luminaire made from powder coated steel sheet. Highly efficient and power saving LED solutions have been used here. The product may be equipped with PMMA opal diffuser, or micro prism diffuser. Luminaire dedicated for module ceilings, recommended to be used in public sectors such as offices, or conference rooms.



Formed, Żywiec


Pictograms:



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
AGAT SLIM LED 2600	2698 / 2840	17	3000 / 4000	591 x 115 x 88
AGAT SLIM LED 4400	4410 / 4644	28	3000 / 4000	591 x 115 x 88
AGAT SLIM LED 5200	5396 / 5680	34	3000 / 4000	1196 x 115 x 88

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
CRI	>80
SDCM	3
Operating temperature range [°C]	5 ÷ 30
Driver	standard (E) DIM DALI (EDD) *

* Variant to specify when ordering

Mechanical features:

Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)

Note: The power shown refers to the whole system (tolerance +/- 10%).

Specifications are subject to change. Pictures of the luminaires may differ from reality.
Date of last update: 13-03-2020