



X-LINE G/K LED

Recessed luminaires



The group of X-line luminaires is made of aluminum profile with opal diffuser or micro-prismatic diffuser. The luminaires may be joined with special connectors providing great freedom in arranging elements of the system and its functionality.



"Artystyczny Żoliborz" residential, Warsaw

Pictograms:



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
X-LINE G/K LED 1300	1349 / 1420	9	3000 / 4000	582 x 80 x 136
X-LINE G/K LED 2200	2205 / 2322	14	3000 / 4000	582 x 80 x 136
X-LINE G/K LED 2600	2698 / 2840	17	3000 / 4000	1142 x 80 x 136
X-LINE G/K LED 3250	3370 / 3550	21	3000 / 4000	1422 x 80 x 136
X-LINE G/K LED 3900	4047 / 4260	26	3000 / 4000	1702 x 80 x 136
X-LINE G/K LED 4400	4410 / 4644	28	3000 / 4000	1142 x 80 x 136
X-LINE G/K LED 5200	5680 / 5396	34	4000 / 3000	2262 x 80 x 136
X-LINE G/K LED 5500	5515 / 5805	35	3000 / 4000	1422 x 80 x 136
X-LINE G/K LED 6600	6615 / 6966	42	3000 / 4000	1702 x 80 x 136
X-LINE G/K LED 8800	8820 / 9288	56	3000 / 4000	2262 x 80 x 136

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
CRI	>80
SDCM	3
Photobiological risk class	RG0
Operating temperature range [°C]	5 ÷ 30
Driver	standard (E) DIM DALI (EDD) *

* Variant to specify when ordering

Mechanical features:

Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA) PLX (PMMA opal)

Note: The power shown refers to the whole system (tolerance +/- 10%).

Specifications are subject to change. Pictures of the luminaires may differ from reality.
Date of last update: 13-03-2020