



X-WALL K9 LED

Surface mounted luminaires



Surface mounted and wall luminaire. Luminaire body made from aluminum profile, its screen made from plastic. Its asymmetric optical system together with the screen provides high energetic efficiency. Luminaire recommended for: hospital bathrooms and wards.



National Research Institute, Warsaw


Pictograms:



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
X-WALL K9 LED 1300	1349 / 1420	9	3000 / 4000	574 x 50 x 60
X-WALL K9 LED 1950	2022 / 2130	13	3000 / 4000	855 x 50 x 60
X-WALL K9 LED 2200	2205 / 2322	14	3000 / 4000	574 x 50 x 60
X-WALL K9 LED 2600	2698 / 2840	17	3000 / 4000	1134 x 50 x 60
X-WALL K9 LED 3250	3370 / 3550	21	3000 / 4000	1415 x 50 x 60
X-WALL K9 LED 3900	4047 / 4260	26	3000 / 4000	1694 x 50 x 60
X-WALL K9 LED 4400	4410 / 4644	28	3000 / 4000	1134 x 50 x 60
X-WALL K9 LED 5200	5396 / 5680	34	3000 / 4000	2255 x 50 x 60
X-WALL K9 LED 5500	5515 / 5805	35	3000 / 4000	1415 x 50 x 60
X-WALL K9 LED 6500	6745 / 7100	43	3000 / 4000	2821 x 50 x 60
X-WALL K9 LED 6600	6615 / 6966	42	3000 / 4000	1694 x 50 x 60
X-WALL K9 LED 8800	8820 / 9288	56	3000 / 4000	2255 x 50 x 60

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
CRI	>80
SDCM	3
Operating temperature range [°C]	5 ÷ 30
Driver	standard (E) DIM DALI (EDD) *

* Variant to specify when ordering

Mechanical features:

Material	aluminum
Color	anodised aluminum
Diffuser	PLX (PMMA opal)

Note: The power shown refers to the whole system (tolerance +/- 10%).

Specifications are subject to change. Pictures of the luminaires may differ from reality.
Date of last update: 13-03-2020