

## Product information

Installation Cable Cat. 7, S/FTP, 4P, 1000 MHz, LSFRZH,  
Cca, 500 m

R833677  
500 m



Premium Cat.7, S/FTP cable. Foil shielding of pairs and overall tin-plated copper braid shield. 100 Ohm impedance. Data transmission frequency of up to 1000 MHz.

020.0983 / similar product

### Technical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Standard	ISO/IEC 11801-1 Ed 1.0 2017-11 EN 50173-1 IEC 61156-5 2 <sup>nd</sup> ed. EN 50288-4-1 IEC 61034 IEC 60754-2 CPR fire class: EN50575 Fire rating: IEC 60332-3-24
Protection class IP	IP 20
Cable type	installation cable
Category	Cat. 7
Shielding	S/FTP
Jacket material	LSFRZH
Outer jacket material	Zero-halogen Flame-retardant Cable, metal-free Zero-halogen Flame-retardant Cable, metal-free
Armour	No protection
Cable overall diameter	Ø 7.2 - 7.5 mm
Conductor	AWG 23
Cable design	normal
Number of wires	8
Stranding	4 pairs
Wire type	Wire
Max. test frequency	1000 MHz
Product code description	Inst C7-S/FTP-4P-3-AWG23-1000MHz-gy-Cca Inst C7-S/FTP-4P-3-AWG23-1000MHz-gy-Cca

## Mechanical Data

DESCRIPTION [UNIT]	VALUE/VALUE RANGE
Cable length	500.0 m / 1640 ft
Color Code RAL	7035 Light gray

Pair-shielded 100 Ohm installation cable with overall braided screen, suitable for transmission frequencies of up to 1000 MHz, 4 x 2 (AWG 23). Compliant with standards ISO/IEC 11801 ed. 2.2, EN 50173-1: May 2011 (DIN EN 50173-1), IEC 61156-5 2nd Ed., EN 50288-4-1, 10GBASE-T in acc. with IEEE 802.3™ Section Four. Low-smoke in acc. with IEC 61034, flame-retardant in acc. with IEC 60332-1 and halogen-free in acc. with IEC 60754-2. Outer jacket color gray, RAL 7035.