



2345 LED

LED wall and ceiling luminaires

- Versatile use
- Optional sensors
- Cover with theft protection

2345 LED is versatile in use. As a wall or ceiling luminaire it fulfils nearly any lighting task thanks to its multi-lumen function with three levels from 1,000 to 2,000 lm. Application areas are corridors, staircases, entrance areas, humid environments and canopied outdoor areas. Do a great job!

Why you'll do a great job with the 2345 LED wall and ceiling luminaire

- Flexible luminaire luminous flux setting (2,000 lm, 1,400 lm and 1,000 lm) thanks to multi-lumen function.
- Fulfils various lighting tasks with only one size.
- High IP protection rating (IP65) for canopied outdoor applications
- Replacement of conventional luminaires in refurbishment cases.
- Theft protection through additional screw locking device
- Optionally with integrated HF motion sensor.

2345 LED at a glance

Dimensions:	Ø 300 x 85 mm
Luminaire luminous flux:	2,000 lm, 1,400 lm, 1,000 lm (Multilumen)
Colour temperature:	3,000, 4,000 K
Connected load:	21 W, 14 W, 11 W
Protection rating, safety class:	IP65, II
Weight:	0.9 kg

All versions of 2345 LED

Product reference	TOC	Luminous flux [lm]	Wattage [W]	Light colour [K]	Dimensions LxWxH [mm]	Replacement
Multilumen (adjustable luminaire luminous flux) with Sensor						
2345 WD1 20/14/10/ML-830 ET IP65 +HFS	7376940	2000 / 1400 / 1000	21 / 14 / 11	3.000	Ø 300 x 85	1 x 36 W TC-F
2345 WD1 20/14/10/ML-840 ET IP65 +HFS	7376740	2000 / 1400 / 1000	21 / 14 / 11	4.000	Ø 300 x 85	1 x 36 W TC-F
Multilumen (adjustable luminaire luminous flux)						
2345 WD1 20/14/10/ML-830 ET IP65	7376840	2000 / 1400 / 1000	21 / 14 / 11	3.000	Ø 300 x 85	1 x 36 W TC-F
2345 WD1 20/14/10/ML-840 ET IP65	7376640	2000 / 1400 / 1000	21 / 14 / 11	4.000	Ø 300 x 85	1 x 36 W TC-F