

BN-2-D

iLight Network to iLight Network Bridge

Key Features

- Configurable as Network Bridge Filter or Repeater
- Enables Larger networks by segmenting long cable runs
- Single control of multiple iCANnet™ networks
- Enables networks to grow beyond 500m of cabling
- Allows larger multi story applications to be installed and commissioned floor by floor
- CE compliant to all relevant standards
- Designed and manufactured to ISO9001 standard

Environmental Data

Temperature Range: 0°C to +50°C

Humidity: 5 - 95% non condensing

Rating: IP20

Mechanical Data

Plastic DINrail housing.

Mounting: DINrail mount with key hole slots for wall mounting if required

Overview

BN-2-D is a DINrail mounted bridging module that allows 2 or more iLight iCANnet™ network segments to be connected together or arranged logically into floors or areas for ease of management. The bridge is also used to extend the network as a repeater where more than 500m of cabling is required or more than 100 network devices are used on one segment. BN-2-D also allows network messages to be filtered to ensure optimal performance in larger networks.

BN-2-D allows multiple network segments to be connected together, enabling up to 65,000 devices to exist on a single system. It also improves reliability of larger systems by isolating and containing any network cabling faults when used correctly.

Electrical Data


Supply: 15V (12-18V) via iCANnet™

May require separate power supply from network supply (eg isolated network backbone configuration)

Network termination: Screw terminals within two part connectors, able to accept 1.5mm² stranded or solid wire.



Dimensions



Contact Us

+44 (0)1923 495495

enquiries@iLight.co.uk

www.iLight.co.uk

iLight

A brand of Signify
Usk House, Llantarnam Park
Cwmbran, NP44 3HD, UK

Changes to the products, to the information contained in this document, and to prices are reserved; so are errors and omissions.

© 2021 Signify Holding
All Rights Reserved

iLight is a registered trademark.
All other trademarks are property of their respective owners.

BN-2-D Rev4 1121